

20FT Platform Container - 28 Ton Payload Capacity

LEN-P-000673



Deck height 323.8 mm - 12.75 inches - and maximum payload 28,680 kg. Those two numbers define what a 20FT platform container is for: oversized, irregular or high-density cargo beyond the dimensional or weight limits of a standard enclosed unit, carried low enough that tall freight still clears road, rail and ocean limits.

MAXIMUM PAYLOAD

28,680 kg

MAXIMUM GROSS WEIGHT

30,480 kg

TARE WEIGHT

1,800 kg**PRODUCT PHOTOS. TECHNICAL DATA. PRACTICAL SELECTION GUIDANCE.**



TECHNICAL PROFILE

20FT Platform Container - 28 Ton Payload Capacity

Published product information. Check the final configuration, supplied equipment and unit-specific documents against the confirmed order.

DETAIL	PUBLISHED SPECIFICATION
Product reference	LEN-P-000673
Product category	20ft Shipping Containers / Platforms and flatracks Shipping Containers
Maximum payload	28,680 kg
Maximum gross weight	30,480 kg
Tare weight	1,800 kg
Platform height	323.8 mm (12.75 in)
External dimensions	6,058 mm × 2,438 mm × 323.8 mm (L×W×H)
Deck material	Steel, 6 mm thick cover plate
Frame structure	Fully welded CORTEN anti-corrosive steel
Twistlocks	ISO standard, integrated



TECHNICAL PROFILE / CONTINUED

20FT Platform Container - 28 Ton Payload Capacity

DETAIL	PUBLISHED SPECIFICATION
Stackable	Yes, when unloaded
Color	RAL 5013 (custom colors available)
The 6 mm deck plate	stands up to point loading and to dynamic force transfer during crane lifts, container movements and heavy freight placement.
An ultra-low platform	at just over 12 inches keeps tall cargo inside clearance limits for road, rail or ocean compliance.
Corner castings and twistlocks	follow ISO alignment and slot into intermodal handling systems - flatbed trucks, railcars, container ships.
CORTEN steel	holds off corrosion long term and resists environmental fatigue, salt-heavy and humid postings included.
Empty units stack	securely, which recovers yard and dockside space during staging and repositioning.
Pre-dispatch inspection	Structural welds, twistlock placement and deck integrity are all verified before a unit is released
Finish	RAL 5013 as standard, with optional custom RAL codes on request
Lead times	In-stock availability, standard delivery turnaround

A CLOSER LOOK



APPLICATION & FIT

Storage, freight handling or the stated container application

Selection checks: Check cargo dimensions against internal size and door opening.; Prepare level supports and adequate delivery and handling space.; Review the stated condition, floor, doors and any specialist equipment..

Does the nominal container length describe usable space?

Nominal length identifies the container format. Internal dimensions and door opening are the relevant checks for cargo fit; use the listed values or request the unit drawing.

Can the unit be used for international freight?

Storage suitability and shipping acceptance are different checks. Where freight service is required, verify the unit identification, condition and applicable inspection documentation.

How are delivery and after-sales terms confirmed?

Delivery charges, availability, return conditions and warranty coverage follow the current company policies and the confirmed order. Use the product reference when contacting the sales desk.

PLAN YOUR ORDER WITH LENOVA GROUP

Quote reference LEN-P-000673. Tell us the application, required configuration and delivery ZIP code.

[View the current product page](#) | [Contact the sales desk](#)

Reference: [Current product information](#). Reviewed 21 October 2026. This brochure is a product guide; the final order specification and current company policies define the supplied scope.