

40FT SHIPPING CONTAINERS / PLATFORMS AND FLATRACKS SHIPPING CONTAINERS

40FT Platform Container - 40 Ton Payload

LEN-P-000674



Deck only. No roof, no sidewalls, nothing above the load line, so freight sits on an exposed flush steel surface and can be reached from every angle. The 40FT Platform Container is a flat-deck, heavy-duty transport unit built to move oversized and ultra-heavy cargo that traditional containers cannot accommodate.

CONTAINER TYPE

40FT Platform - flat deck, no roof or walls

PAYLOAD CAPACITY

Over 40 metric tons (40,520 kg)

CONSTRUCTION

Stackable CORTEN steel frame with high-tensile flush steel deck

PRODUCT PHOTOS. TECHNICAL DATA. PRACTICAL SELECTION GUIDANCE.



TECHNICAL PROFILE

40FT Platform Container - 40 Ton Payload

Published product information. Check the final configuration, supplied equipment and unit-specific documents against the confirmed order.

DETAIL	PUBLISHED SPECIFICATION
Product reference	LEN-P-000674
Product category	40ft Shipping Containers / Platforms and flatracks Shipping Containers
Container type	40FT Platform - flat deck, no roof or walls
Payload capacity	Over 40 metric tons (40,520 kg)
Construction	Stackable CORTEN steel frame with high-tensile flush steel deck
Loading profile	Low deck height (480 mm) for efficient crane and forklift compatibility
Twistlocks	Built-in for direct cargo lashing
Finish	Standard RAL5013 - custom coatings available upon request
External dimensions (L × W × H)	12,192 mm × 2,438 mm × 480 mm (40' × 8' × 1.57')
Deck height	480 mm (low-profile loading)



TECHNICAL PROFILE / CONTINUED

40FT Platform Container - 40 Ton Payload

DETAIL	PUBLISHED SPECIFICATION
Tare weight	4,480 kg
Max payload	40,520 kg
Max gross weight	45,000 kg
Deck material	High-tensile flush steel
Structure	Stackable CORTEN steel frame
Built-in twistlocks	Yes - integrated securing points
Heavy equipment and machinery.	Designed for the secure transit of excavators, dozers, oversized trucks or tracked vehicles.
Project cargo logistics.	Turbines, generators, transformers and structural components that exceed general ISO container limits.
Oversized freight.	Irregular loads such as steel beams, oilfield skids, container-mounted gensets or long-span assemblies.
Yard storage and static use.	A stable elevated base for temporary machinery, mobile staging or remote-site equipment deployment.
deck integrity	tch, every unit is inspected for deck integrity , corner alignment and twistlock tension

A CLOSER LOOK



APPLICATION & FIT

Storage, freight handling or the stated container application

Selection checks: Check cargo dimensions against internal size and door opening.; Prepare level supports and adequate delivery and handling space.; Review the stated condition, floor, doors and any specialist equipment..

Does the nominal container length describe usable space?

Nominal length identifies the container format. Internal dimensions and door opening are the relevant checks for cargo fit; use the listed values or request the unit drawing.

Can the unit be used for international freight?

Storage suitability and shipping acceptance are different checks. Where freight service is required, verify the unit identification, condition and applicable inspection documentation.

How are delivery and after-sales terms confirmed?

Delivery charges, availability, return conditions and warranty coverage follow the current company policies and the confirmed order. Use the product reference when contacting the sales desk.

PLAN YOUR ORDER WITH LENOVA GROUP

Quote reference LEN-P-000674. Tell us the application, required configuration and delivery ZIP code.

[View the current product page](#) | [Contact the sales desk](#)

Reference: [Current product information](#). Reviewed 21 October 2026. This brochure is a product guide; the final order specification and current company policies define the supplied scope.