

40FT SHIPPING CONTAINERS / NEW SHIPPING CONTAINERS

# 40FT High Cube Open Side Shipping Container (One Trip)

LEN-P-000695



Side access runs almost the entire length of this unit: close to 38 feet of continuous side access , with the conventional rear double doors retained at the end. It is a 40FT high cube open side container in one-trip condition, fabricated from CORTEN anti-corrosive steel and floored with high-performance Keruing-Apitong marine-grade plywood . Internal volume.

## CONDITION

**New, one-trip only**

## CONSTRUCTION

**CORTEN anti-corrosive steel**

## REAR ACCESS

**Double cargo doors on cam-lock mechanisms**

PRODUCT PHOTOS. TECHNICAL DATA. PRACTICAL SELECTION GUIDANCE.



# TECHNICAL PROFILE

## 40FT High Cube Open Side Shipping Container (One Trip)

Published product information. Check the final configuration, supplied equipment and unit-specific documents against the confirmed order.

| DETAIL                          | PUBLISHED SPECIFICATION                                  |
|---------------------------------|----------------------------------------------------------|
| Product reference               | LEN-P-000695                                             |
| Product category                | 40ft Shipping Containers / New Shipping Containers       |
| Condition                       | New, one-trip only                                       |
| Construction                    | CORTEN anti-corrosive steel                              |
| Rear access                     | Double cargo doors on cam-lock mechanisms                |
| Side access                     | Full-length swing doors, with no center post obstruction |
| Flooring                        | 28mm thick, 19-ply Keruing-Apitong marine plywood        |
| Mobility                        | Forklift pockets built in for static repositioning       |
| Ventilation                     | Two weatherproof vents                                   |
| Security                        | Integrated lockbox with 36" locking bar handles          |
| External dimensions (L × W × H) | 40' × 8' × 9'6"                                          |
| Internal dimensions (L × W × H) | 39'5" × 7'6" × 8'1"                                      |
| Side door opening               | 37'10" L × 7'6" H                                        |



# TECHNICAL PROFILE / CONTINUED

## 40FT High Cube Open Side Shipping Container (One Trip)

| DETAIL                               | PUBLISHED SPECIFICATION                                                                                                                                              |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear door opening                    | 7'3" W × 7'10" H                                                                                                                                                     |
| Tare weight                          | 14,510 lbs                                                                                                                                                           |
| Max payload                          | 52,690 lbs                                                                                                                                                           |
| Gross weight rating                  | 67,200 lbs                                                                                                                                                           |
| Side door system.                    | With no center post in the way, the full wall opens for forklifts, cranes or custom conversion work.                                                                 |
| CORTEN steel construction.           | Engineered for longevity outdoors, with rust resistance and durability under weather exposure.                                                                       |
| Marine-grade flooring.               | The 28mm Apitong plywood deck resists moisture, impact and degradation over time.                                                                                    |
| Ventilation and seal integrity.      | Regulated airflow is supported, and internal condensation is kept in check.                                                                                          |
| Locking mechanisms.                  | Industrial-grade hinges and handles, rated for high-frequency usage.                                                                                                 |
| Oversized equipment loading.         | Takes long, wide or awkwardly shaped cargo - mechanical assemblies, HVAC units, pipe systems - through a full-width side opening reachable by forklift or boom lift. |
| Industrial and warehouse logistics.  | Speeds up inventory staging and cross-dock work in operations where rear-only loading creates a bottleneck.                                                          |
| On-site walk-in storage.             | Dual access gives aisle-style entry, which keeps tool and parts management efficient where job site space is tight.                                                  |
| Modular conversions and fabrication. | A common base for builds needing side exposure, window insertions or full-wall visibility: container homes, cafes and offices.                                       |

# A CLOSER LOOK



## APPLICATION & FIT

Storage, freight handling or the stated container application

Selection checks: Check cargo dimensions against internal size and door opening.; Prepare level supports and adequate delivery and handling space.; Review the stated condition, floor, doors and any specialist equipment..

### **Does the nominal container length describe usable space?**

Nominal length identifies the container format. Internal dimensions and door opening are the relevant checks for cargo fit; use the listed values or request the unit drawing.

### **Can the unit be used for international freight?**

Storage suitability and shipping acceptance are different checks. Where freight service is required, verify the unit identification, condition and applicable inspection documentation.

### **How are delivery and after-sales terms confirmed?**

Delivery charges, availability, return conditions and warranty coverage follow the current company policies and the confirmed order. Use the product reference when contacting the sales desk.

## PLAN YOUR ORDER WITH LENOVA GROUP

Quote reference LEN-P-000695. Tell us the application, required configuration and delivery ZIP code.

[View the current product page](#) | [Contact the sales desk](#)

Reference: [Current product information](#). Reviewed 21 October 2026. This brochure is a product guide; the final order specification and current company policies define the supplied scope.