

20FT SHIPPING CONTAINERS

20FT One Trip Open Side Shipping Container

LEN-P-002008



The 20FT One Trip Open Side Shipping Container offers unmatched versatility and access. Manufactured as a one-trip unit, it maintains like-new structural integrity while providing premium design enhancements for users handling oversized, oddly shaped, or high-frequency cargo operations.

FEATURE

Specification

CONDITION

One Trip (New)

MATERIAL

CORTEN anti-corrosive steel

PRODUCT PHOTOS. TECHNICAL DATA. PRACTICAL SELECTION GUIDANCE.



TECHNICAL PROFILE

20FT One Trip Open Side Shipping Container

Published product information. Check the final configuration, supplied equipment and unit-specific documents against the confirmed order.

DETAIL	PUBLISHED SPECIFICATION
Product reference	LEN-P-002008
Product category	20ft Shipping Containers
Feature	Specification
Condition	One Trip (New)
Material	CORTEN anti-corrosive steel
Flooring	28mm Keruing-Apitong marine-grade plywood
Rear Doors	Standard cargo doors with ISO-certified seals
Side Doors	Full-length segmented side access (19'2" span)
Security	Integrated lockbox for padlock
Ventilation	Four weatherproof passive vents
Forklift Pockets	Dual entry forklift access points
Locking Mechanism	ISO-standard heavy-duty locking bars
Measurement Point	Value



TECHNICAL PROFILE / CONTINUED

20FT One Trip Open Side Shipping Container

DETAIL	PUBLISHED SPECIFICATION
Exterior (L × W × H)	20' × 8' × 8' 6"
Interior (L × W × H)	19' 4" × 7' 6" × 7' 6"
Rear Door Opening (W × H)	7' 3" × 7' 2"
Side Door Opening (L × H)	19' 2" × 7' 2"
Tare Weight	7,010 lbs
Payload Capacity	60,190 lbs
Gross Weight	67,200 lbs
Segmented Full Side Doors	Hinged in multiple panels, the side access allows selective or full-length loading, maximizing operational control for unconventional freight.
Marine-Grade Flooring	28mm Keruing-Apitong hardwood resists rot, delamination, and mechanical abrasion - ideal for industrial loads or modification bases.
Forklift Compatibility	Integrated forklift channels offer safe, centered transport across uneven surfaces or tightly spaced job sites.
Weatherproof Design	All vents and seams are sealed to prevent water ingress, with four passive vents maintaining airflow to mitigate condensation buildup.
Built-in Security Lockbox	All door systems include anti-tamper locking bar compatibility and ISO-standard steel lockboxes.
Side Hinge Testing	Full articulation, torsion alignment, and latch integrity checks

A CLOSER LOOK



APPLICATION & FIT

Storage, freight handling or the stated container application

Selection checks: Check cargo dimensions against internal size and door opening.; Prepare level supports and adequate delivery and handling space.; Review the stated condition, floor, doors and any specialist equipment..

Does the nominal container length describe usable space?

Nominal length identifies the container format. Internal dimensions and door opening are the relevant checks for cargo fit; use the listed values or request the unit drawing.

Can the unit be used for international freight?

Storage suitability and shipping acceptance are different checks. Where freight service is required, verify the unit identification, condition and applicable inspection documentation.

How are delivery and after-sales terms confirmed?

Delivery charges, availability, return conditions and warranty coverage follow the current company policies and the confirmed order. Use the product reference when contacting the sales desk.

PLAN YOUR ORDER WITH LENOVA GROUP

Quote reference LEN-P-002008. Tell us the application, required configuration and delivery ZIP code.

[View the current product page](#) | [Contact the sales desk](#)

Reference: [Current product information](#). Reviewed 21 October 2026. This brochure is a product guide; the final order specification and current company policies define the supplied scope.