



20FT SHIPPING CONTAINERS

20FT All Side Open Shipping Container (8'6")

LEN-P-002010



The 20FT All Side Open Shipping Container (8'6") redefines access flexibility with fully functional doors on all four sides - left, right, rear, and front. Designed for high-performance operations that demand rapid load cycles, this unit simplifies access for forklifts, cranes, and labor crews without repositioning cargo.

FEATURE

Description

DOOR ACCESS

Hinged access on all four sides with gasket-sealed door panels

FLOORING

28mm marine-grade plywood, moisture and impact resistant

PRODUCT PHOTOS. TECHNICAL DATA. PRACTICAL SELECTION GUIDANCE.



TECHNICAL PROFILE

20FT All Side Open Shipping Container (8'6")

Published product information. Check the final configuration, supplied equipment and unit-specific documents against the confirmed order.

DETAIL	PUBLISHED SPECIFICATION
Product reference	LEN-P-002010
Product category	20ft Shipping Containers
Feature	Description
Door Access	Hinged access on all four sides with gasket-sealed door panels
Flooring	28mm marine-grade plywood, moisture and impact resistant
Locking Mechanism	Double-high locking gear on all access points
Security	Welded lockbox for secure padlocking
Ventilation	Weatherproof passive vents for internal airflow
Handling	Integrated forklift pockets and stackable corner castings
CSC Plate	Certified for international logistics and intermodal stacking
Attribute	Specification
External Dimensions	20' L × 8' W × 8' 6" H



TECHNICAL PROFILE / CONTINUED

20FT All Side Open Shipping Container (8'6")

DETAIL	PUBLISHED SPECIFICATION
Internal Dimensions	19' 4" L × 7' 8" W × 7' 10" H
Each Door Opening (W × H)	Approx. 7' 8" × 7' 5" per panel
Tare Weight	~5,350 lbs
Gross Weight	67,200 lbs
Payload Capacity	~61,850 lbs
CORTEN Weathering Steel	Provides long-term structural integrity in corrosive, wet, or chemically active environments.
Four-Sided Door System	Enables complete 360° cargo access, eliminating bottlenecks caused by rear-only loading.
High-Tensile Hinges & Locking Rods	Designed for repetitive mechanical use with enhanced leverage for smoother operation.
Event-Ready Form Factor	Easy to brand, modify, or integrate with modular scaffolding or retail-ready façades.
ISO Compliant	Standard dimensions for universal stacking and crane mounting
Forklift Pocket Tested	Compatible with both heavy-duty and standard yard equipment
Weatherproofing Inspection	Gasket pressure, hinge seal alignment, and venting performance tested before dispatch
Optional Finishes	Available with anti-graffiti coating, RAL custom paint, or logo imprint upon request

A CLOSER LOOK



APPLICATION & FIT

Storage, freight handling or the stated container application

Selection checks: Check cargo dimensions against internal size and door opening.; Prepare level supports and adequate delivery and handling space.; Review the stated condition, floor, doors and any specialist equipment..

Does the nominal container length describe usable space?

Nominal length identifies the container format. Internal dimensions and door opening are the relevant checks for cargo fit; use the listed values or request the unit drawing.

Can the unit be used for international freight?

Storage suitability and shipping acceptance are different checks. Where freight service is required, verify the unit identification, condition and applicable inspection documentation.

How are delivery and after-sales terms confirmed?

Delivery charges, availability, return conditions and warranty coverage follow the current company policies and the confirmed order. Use the product reference when contacting the sales desk.

PLAN YOUR ORDER WITH LENOVA GROUP

Quote reference LEN-P-002010. Tell us the application, required configuration and delivery ZIP code.

[View the current product page](#) | [Contact the sales desk](#)

Reference: [Current product information](#). Reviewed 21 October 2026. This brochure is a product guide; the final order specification and current company policies define the supplied scope.